



TRANSIT FLOOR COVERINGS

H A LATEULERE AND COMPANY (NATAL) (PTY) LTD

RECOMMENDED ADHESIVES FOR THE INSTALLATION OF TRANSIT PRODUCTS

		PEKAY	QUALICHEM
NOTE:	To avoid rising moisture in concrete floors having no fitted damp-proof membrane (in some cases domestic garages) a floor sealer is recommended.	G657 PRIMER	QAR280
1	ACRYLIC adhesive for normal use and, for extra strength	WD91 WD90	QAR190A
	For use on an old bitumen surface the SOLVENT-FREE adhesive.	WD98XE	QAR126C
2	CONTACT adhesive for wooden floors, walls, steel floors and lifts.	V435 (Normal) V440 (Non flammable)	QAN400
3	POLYURETHANE adhesive for wet areas such as ablution blocks and where there is constant water spillage, where floor surface temperature is increased considerably due to direct sunlight eg floors adjacent to plate glass windows and sun lounges etc. Floors subject to torque stresses from turning wheels.	A660	QAR209C
4	CONDUCTIVE adhesive <u>only</u> for conductive tiles.	Conductive A659AS	

PO BOX 8298
1406 ELANDSFONTEIN
SOUTH AFRICA

3 BUNDO ROAD
SEBENZA
EDENVALE

TELEPHONE 0861 TRANSIT / 0861 872 674
TELEFAX 086 670 8110
EMAIL info@transittiles.com
WEBSITE www.transittiles.com